

ARTICLE

Daylight Signal Lamp - Wiska - HML-ISO 35-5-B-W-F00-A01 - MED/SOLAS

Number: 7.01.0076

SPECIFICATIONS

Weight: 9,50 kg
Made in: Germany
HS Code: 85318070

DESCRIPTION

Type: HML-ISO 35-5-B-W-F00-A01
Material: Polyamide, fibre reinforced
Material globe/diffuser: Polycarbonate
Colour: Black
Wattage: 30 W
Voltage min. (V): 12 V
Voltage max. (V): 24 V
Type of Voltage: DC
Protection class: IP56
Operational areas: Outdoor, Emergency
Temp. range min: -25 °C
Temp. range max: 55 °C
Lightsource: Halogen lamp
Reflector: Glass
Lightsource incl.: Yes
Bulb shape: reflector
Average lamp durability: 4000 h
Globe colour: Clear
Light performance: immediately
Lampholder: GY6,35
Number of lampholder: 1 ST
Material cable gland: Polyamide
Power cable: H07RN-F 2x1,5mm²
Ø cable diameter min: 6 mm
Ø cable diameter max: 13 mm
External dimensions LxWxH: 160 x 244 x 215 mm
Approval: DNV-GL
Weight: 9,5 kg
Equipment: without filter, incl. PowerPack + Charger
Advice: Bag
Tariff number: 85318070

Remarks:

- Signal range: 3.400m during the day, 21.400m at night

Equipment:

- Toughened front glass
- Rubber sealing
- Quick fastening rubber
- Sighting device
- Micro switch for left- and right hander
- mounted halogen lamp + 3 spare lamps
- Connection cable 5m
- SOS function
- Permanent light function
- Cargo and storage in a robust, hydrophobic bag
- This device is built at least according to requirements of ABS, BV, DNV, GL, LR, PRS

CERTIFICATIONS



- MED
- SOLAS
- RED ENSIGN/MER (UK Approval)

SPARE PARTS / COMPLEMENTARY GOODS

- 2.40.0031 Battery Power Pack for Daylight Signal Lamp Wiska HML-ISO-35
- 2.40.0032 Charger 230V/50-60 Hz for Power Pack HML-ISO-35
- 7.01.0080 Socket DK503 - for Daylight Signal Lamp - Wiska