DATASHEET

ARTICLE

Firehose WHITE - aluminium Storz C/52 - Lug 66 - 2 inch / 52mm x 15mtr - MED/SOLAS

Number: 4.05.0021

SPECIFICATIONS

Made in: Germany

HS Code: 59090010

DESCRIPTION

Fire fighting hose for shipboards according to DIN EN 14540 (MED approval)

Inner lining:
Two-component system consisting of black SBR-rubber and white NBR-adhesive

Jacket:
100 % Polyester high tenacity yarn, circular woven, warp threads 2-ply twisted, plain weave

Characteristics:
abrasion resistant, lightweight and flexible, ageing and ozone resistant, external resistance to oil, fuel and chemical products

Temperature:
Cold resistant to - 30 °C
Heat resistant up to + 100 °C (temporarily higher)

Max. pressure 60 bar
Working pressure 15 bar

CERTIFICATIONS

- [x] SOLAS
- [x] MED

SPARE PARTS / COMPLEMENTARY GOODS

4.05.0140 Coupling Spanner for Storz - with frost protected grip - Lug 66-81
4.05.1110 Nozzle HS12 - 2" BSP male thread - incl brass Storz C/52 coupling - Lug 66 - MED/SOLAS
4.05.1111 Nozzle HS16 - 2" BSP male thread - incl brass Storz C/52 coupling - Lug 66 - MED/SOLAS
4.05.1112 Nozzle HS19 - 2" BSP male thread - incl brass Storz C/52 coupling - Lug 66 - MED/SOLAS

Datema Delfzijl B.V. tel: +31 596 635252 e-mail: sales@datema.nl