DATASHEET



ARTICLE

Comet Floating Smoke Signal - Orange - 9192000 - MED/SOLAS

Number: 3.05.0069 IMPA number: 331380

SPECIFICATIONS

Measurements: 82 (I) x 82 (w) x 114 (h) mm

Weight: 0,36 kg

Made in: Germany

HS Code: 36049000

DESCRIPTION

The Smoke Signal Orange is a compact, daylight distress signal designed to be easy and safe to handle. It provides effective position marking during rescue operations and can be used to indicate wind direction, producing dense orange smoke for a minimum of 3 minutes.

Application

The Comet orange smoke signal is a small and compact distress signal

for daylight use designed for stowage in liferafts and lifeboats. SOLAS requires 2 smoke signals per raft/boat.

- · Signal for position marking during rescue operations
- · Indicates wind direction
- · Safe use on oil or petrol covered water
- · Conforming to SOLAS 74 as amended
- · Ideal also for leisure boats

Operation

- 1. Remove plastic cap. Point away from body.
- 2. Pull tab firmly away from canister. Ensure hand remains clear of $\ensuremath{\mathsf{HOT}}$ END.
- 3. Throw Lifesmoke overboard immediately. Smoke will be emitted after
- a 2 second delay.

Packing & Transport Information

- 24 signals in 1 fibreboard box
- Gross weight 9.40 kg (20.72 lb.)
- Net weight 8.90 kg (19.62 lb.)
- Measurements of fibreboard box: 37 x 27 x 27 cm (15 x 11 x 11 in)
- Net Explosive Content per box: 5.736 kg (12.64 lb.)
- Hazard Class 1.4S
- UN 0507
- Proper Shipping Name: Signals, Smoke
- Other Information: Passenger and Cargo Aircraft



DATASHEET



Specifications

• Height: 114 mm (4.5 in)

• Diameter: 82 mm (3.2 in)

• Gross Weight Max. 370g (13.05 oz)

• NEC Max. 239g (8.43 oz)

• Burning time: 3 minutes minimum

• Colour of smoke: orange

· Ignition: percussion ignitor with 2 seconds safety delay

Storage

This compact unit is ideally stored in a water-resistant locker at ambient

temperature allowing easy access in an emergency or in the robust, specially designed polybottle.

Approvals

Conforms to SOLAS 74 as amended, Res. MSC 81 (70). Approvals: CE 0589, BAM–P1-0191, 0589-P1-0324, BGV MED 423.008, USCG 160.122./21/0, 160.022/21/0, and other major maritime authorities worldwide. 0507

CERTIFICATIONS



✓ SOLAS