

ARTICLE

Shore connection box - including international shore connection

Number: 7.80.0036

SPECIFICATIONS

Measurements: 70 (l) x 260 (w) x 285 (h) mm

Weight: 7,00 kg

Made in: China

HS Code: 74199990

<div><div>Product description</div><div>Designed to last in the tough marine environment. BMC glass fiber polyester box, flame retardant. Cabinet door can be opened both the right and left direction. Stainless steel lock and hinges. Brass international shore connection with 2" thread. SafeSign sign with 5 year warranty, even on outdoor use.</div></div>	<div><div>Pictures</div><div></div></div>								
<div><div>Dimensions</div><div>Art.no: ICS80NCOMPL Dimensions: 285x260x70 mm</div><table><tr><th>Width</th><th>Height</th><th>Length</th><th>Weight</th></tr><tr><td>260 mm</td><td>285 mm</td><td>70 mm</td><td>7 kg</td></tr></table><div>1.0N /mm max pressure</div><div>HS code: 3923101000</div></div>	Width	Height	Length	Weight	260 mm	285 mm	70 mm	7 kg	<div><div>Certificates & Standards</div><div></div></div>
Width	Height	Length	Weight						
260 mm	285 mm	70 mm	7 kg						

DESCRIPTION

What is an International Shore Connection?

The goal of the International Shore Connection is to keep a standby hose attachment to get a connection from shore or from other ships for onboard firefighting, in case there is a total failure of pumps onboard.

While using the International Shore Connection, the sea water is supplied at a pre-decided pressure and is connected to the ship's fire main. You should keep this international shore connection flange at a convenient and accessible location (Bridge or in the Fire locker) of a ship so that in case of an emergency it is ready to use.

Make the connection of steel or other suitable material and design it for 1.0 N/mm² services. Make sure the flange has a flat surface on one side. You must connect the other side to a coupling that you can easily fit into a ship's hydrant and/or hose connection.

You have to keep the connection onboard with a ready gasket of material that can handle a pressure of 1.0 N/mm² together with four 16mm bolts, 50 mm in length, and eight washers so that the connection can be readily used in case of an emergency situation.

Complete set: Box + Flange + Sign. Designed to last in the tough marine environment.

- BMC glass fiber polyester box, flame retardant.
- Cabinet door that you can open in both the right and left direction.
- Stainless steel lock and hinges.
- Brass international shore connection with 2" thread.
- SafeSign sign with 5-year warranty, even on outdoor use.