DATASHEET

ARTICLE

Turbo Spritze AWG 2235-C Gold - MED/SOLAS

Number: 4.05.0606

SPECIFICATIONS

Measurements:	290 (l) x 112 (w) x 245 (h) mm
Weight:	2,30 kg
Made in:	Germany
HS Code:	84242000

DESCRIPTION

Turbo Spritze AWG 2235-C Gold
Certified for marine firefighting and firefighting on ships, the AWG Turbo-Nozzle GOLD is lightweight and generous when it comes to power and practical suitability – qualified for saltwater, is corrosion-resistant and intuitively usable.

System Inlet: Storz
Size Inlet: 52 (C)
Inlet: Storz 52 (C)
Inlet swiveling: Yes
Nominal size: 2235
Flow rate at reference pressure p1 [lpm]: 60 / 130 / 235
Reference pressure p1 [bar]:6
throw distance at reference p1 [m]: 18-26-30 (full jet), 7-13 (spray jet)
max. permissible operating pressure [bar]: 16
Spray angle [°]: 0 - 120
Turbo wheel: Yes
Handle: Yes
Product colour: Gold; Black
Material adapter: Aluminum
Applicable Standard: DIN EN 15182 and ISO 9227-NSS approved

CERTIFICATIONS

- [x] MED
- [x] SOLAS

Datema Delfzijl B.V. tel: +31 596 635252 e-mail: sales@datema.nl