# **DATASHEET**



### **ARTICLE**

Gasdetector Honeywell BW Clip O2 (zuurstof)

Number: 4.29.0139

## **SPECIFICATIONS**

Made in: United Kingdom

HS Code: 90271010



# DATASHEET



### **DESCRIPTION**

Gasdetector Honeywell BW Clip O2 (zuurstof)

Honeywell BW Clip Single Gas Detector - Maintenance-Free Protection Against Gas Hazards

The Honeywell BW Clip is a maintenance-free, single-gas detector with a fixed 2-year lifetime — the most widely used single-gas detector in industrial environments. Available as an H2S alarm, CO detector (with continuous display), or O2 meter (without continuous display), it's designed to meet the specific needs of the user.

No calibration or sensor replacement required. Rugged, water-resistant (IP66/67), and approved for ATEX Zone 0.

Ready for immediate use, equipped with clear visual, audible, and vibration alarms.

Reliable Gas Detection - Wherever You Work

The Honeywell BW Clip is a portable, single-gas detector with a fixed operational life of 2 years (also available in a 3-year version for CO).

This maintenance-free device continuously monitors oxygen (O2), carbon monoxide (CO), or hydrogen sulfide (H2S) — providing simple, reliable protection for workers across industries such as construction, installation technology, and waste management.

#### **Key Features**

- Maintenance-free design - No sensor replacement, calibration, or recharging needed for the entire 2year lifespan (3 years for CO model).

Ready to use – Activate and start measuring immediately; no setup required.

Clear alarms - Audible (up to 95 dB), visual, and vibration alarms alert the user to dangerous gas levels.

- Gas concentration display The CO detector provides a continuous digital reading. The O2 meter and H2S alarm activate only when hazardous levels are detected.
- Rugged and reliable Water- and dust-resistant housing with IP66/67 rating, suitable for tough industrial environments.

Event logging – Records up to 35 events for later review or compliance analysis.

- ATEX Zone 0 certified – Safe for use in potentially explosive atmospheres.

Optional hibernation case - Extends the life of the CO detector and H2S alarm by up to one additional year when used intermittently.

### **CERTIFICATIONS**



✓ SOLAS