## **DATASHEET**



## **ARTICLE**

Fall arrest Kratos Triton - retractable - ATEX 1 - 30mtr

Number: FA2041030

## **SPECIFICATIONS**

Measurements: 362,1 (I) x 325,9 (w) x 220,4 (h) mm

Weight: 20,17 kg
Made in: France
HS Code: 84798997

## **DESCRIPTION**

Fall arrest Kratos Triton - retractable - ATEX 1 - 30mtr

TRITON, sealed retractable fall arrester, stainless steel wire rope 30 m

- Casing made up of high impact strength Polymer with Stainless steel cover, integrated carrying handle.
- The design of the internal mechanism in 2 different parts allows a perfect impermeability (meets IP68 level of IEC 60529) of the blocking-braking system. As for the pulley & wire rope part, it allows to replace the wire rope quickly & easily with minimum tools.
- Comes with Stainless Steel Wire Rope of diam 4.5 mm having:
- ==> a stainless steel connector with load indicator
- ==> a gripping handle.
- Internal braking mechanism to reduce the fall arrest force to less than 6 kN.
- 180°-pivoting anchorage loop & FA 50 106 22 stainless steel connector at anchorage end.
- Weight: 20.70 kg.
- Delivered with a cord (FA 20 904 30) for guiding the winding back of the wire rope.
- HS code: 84798997

Compliance: EN 360:2002, IEC 60529 (IP68), ATEX Zone 1.

Minimum breaking strength > 12 kN.

Approved for a user with a max. weight of 140 kg in vertical use only.

