DATASHEET

ARTICLE

Gasdetector Teledyne PS200 4-gas (LEL/O2/H2S/CO) - pumped - MED/SOLAS

Number: 4.27.0505

SPECIFICATIONS

Measurements: 121 (l) x 59 (w) x 32 (h) mm

Weight: 0,23 kg

Made in: United Kingdom

HS Code: 90271010

DESCRIPTION

Multi-gas detector GMI PS 200, 4-gas LEL/O2/H2S/CO pumped, supplied complete with quick operating guide, universal charger / communications cable, three meters sampling line and connector.
Not suitable for inert/infrared measurements (in inert spaces)

- Temperature -20C to +50C (-4F to 122F)
- Alarms: Highly visible flashing LED, piercing >90dB audible
- Display: Green and red LCD backlight display
- Battery: Charging Time < 4 hrs
- Drop Test: 3 m
- IP Rating: IP67 (Dust-tight and waterproof to 1m)

Required
3481

CERTIFICATIONS

- [x] MED
- [x] SOLAS
- [x] ATEX

SPARE PARTS / COMPLEMENTARY GOODS

4.27.0010 Sampling hose for distant measuring, per metre
4.27.1072 Sample Line Connector
4.27.1077 Regulator demand flow (brass) - can be used for aut. calibration station
4.27.1078 Calibration 4-gas mixture
4.27.1086 Calibration hose - 1 meter
4.27.2000 Aluminium carrying case for gasdetection equipment