

# DATASHEET



## ARTICLE

### Portable foam applicator HV225 S LX pipe 225 lt. per min.

Number: 4.05.0175

IMPA number: 331076



## SPECIFICATIONS

Measurements: 769 (l) x 113 (w) x 98 (h) mm

Weight: 2,75 kg

Made in: United Kingdom

HS Code: 84242000

## DESCRIPTION

Portable foam applicator HV225S LX Foam Brass Pipe, capacity 225 lt./min., light alloy with suction hose and Storz connector lug 66mm / 2", powder coated (Hi Viz Yellow)

The Delta HV-Series of Foam Branchpipes have been designed for use with all foam types including Fluoroproteins, AFFF's, FFFP's and All-Purpose Alcohol Resistant foams. Designed to first expand and then accelerate the foam to high velocity the HV-Series is capable of long throws beyond the range of many older designs. Standard models are designed for use in conjunction with Delta Z-Series Variable Foam Inductors and Self-Inducing models with quick release pick-up sticks are also available for foam induction direct from the drum. Manufactured by Delta in the UK the HV-Series has a light alloy body, powder-coated inside and out for resistance to corrosion. Finished in epoxy coated polyester International Orange or High-Viz Yellow the HV-Series can be supplied with a wide range of International inlet adaptors for compatibility to existing hoselines.

- Nominal Flow L/Min 5 Bar = 200 ltr
- Nominal Flow L/Min 7 Bar = 225 ltr
- Foam expansion = 6-10
- Length = 740mm
- Weight = 2.2kg
- Self inducing models
- Suitable for all foams
- Range 18 -22 meters at 7 bar
- Inlet: 2" BSP Male + Storz C (ØA 66mm) Brass

## CERTIFICATIONS

SOLAS

## SPARE PARTS / COMPLEMENTARY GOODS

4.05.0189 Foam-making liquid BIO ECOPOL F3HC - 20Ltr - PFAS free