

ARTICLE

Transceiver Entel HT649 - GMDSS Package 2

Number: 2.50.0000

SPECIFICATIONS

Measurements: 59,5 (l) x 130 (w) x 37 (h) mm

Weight: 0,28 kg

Made in: Philippines

HS Code: 85256000

DESCRIPTION

Portofoon GMDSS HT649 package 2, including: GMDSS battery, CNB 750 battery (Lithion/Ion) and Charger

- Environmental protection to IP68 (2 meters for 4 hours)
- Battery Type: Primary
 - Lithium Secondary
 - 2000 mAh Li-Ion
- Frequency Range: 156 - 163.275MHz
- Channels: 19 INT, USA & CAN Marine Channels
- Channel Spacing: 25 kHz
- Communication Method: Simplex / semi duplex
- Antenna Impedance: 50 ohm
- Power Supply Voltage: 7.4V DC
- Current Drain (nominal): 40mA
- Microphone: Internal condenser microphone
- Primary Duty Cycle (10/10/80) > 8 Hours
- Secondary Duty Cycle (5/5/90): 14.5 hours
- Operating Temperature: -20° to +55°C
- Construction: MIL-STD 810C/D/E/F



CERTIFICATIONS

- MED
- SOLAS

SPARE PARTS / COMPLEMENTARY GOODS

9.10.0618 Programming channels