

ARTICLE

Lifebuoy Light Daniamant L161 - LED - incl.bracket - ATEX - MED/SOLAS

Number: 3.05.0350

IMPA number: 330330

SPECIFICATIONS

Measurements: 185 (l) x 106 (w) mm

Weight: 0,30 kg

Made in: United Kingdom

HS Code: 85318070



DESCRIPTION

The L161 is fully approved to SOLAS/MED standards and also ATEX, IECEx and ETL listing under UL913. It is intrinsically safe (category 1) and as such is suitable for use in hazardous zones 0, 1 and 2. The L161 is our new intrinsically safe Lifebuoy Light and replaces the well-established L40 Light.

Fit and Forget

All Lifebuoy Lights offer a five year life. No maintenance or replacement batteries are required. This saves time and expense during inspections.

Compact size

These Lifebuoy Lights are amongst the smallest and lightest lights available on the market today.

76 Metres Drop Height

MED/SOLAS and USCG standards call for the Lifebuoy lights to be dropped from 30 metres. All these Lifebuoy lights have passed a drop height test from 76 metres high. This makes these new lifebuoy lights suitable for use on any platform or vessel with high bridge wings.

Mounting made easy

All Lifebuoy Lights are supplied with a unique mounting bracket, enabling easy fitting in all locations.

LED Technology

Lifebuoy Lights are using the latest advances in LED technology. They feature very low current consumption and enhanced reliability. All our Lifebuoy Lights feature a flashing light.
3091

CERTIFICATIONS



MED



SOLAS



ATEX